

CRACK FILLER

USES

Cosmetically fills cracks in the following concrete surfaces:

- BROWN on Exposed Pea Gravel Concrete
- GRAY on Exposed Gray Chipped Limestone Concrete
- WHITE(Light Gray) on Broomed Swept Concrete

DESCRIPTION

Clemons **CRACK FILLER** cosmetically repairs scars, gouges, and cracks in outdoor concrete surfaces. This crack filler will match the texture, color and appearance of specified concrete surfaces. Using this product and appropriate Clemons concrete sealer makes the crack virtually disappear. Clemons **CRACK FILLER** must be sealed for maximum blending and longevity. For a more structural repair, fill crack with epoxy or exterior caulk before topping with Clemons **CRACK FILLER**. 1 quart will fill approximately 100 ft. of normal cracks.

APPLICATION

1. Clean concrete well with a power washer.
2. SHAKE WELL!
3. Remove cap and snip spout to desired width of pour.
4. Pour Clemons **CRACK FILLER** into crack. Concrete can be damp but crack should be sufficiently dry so there is no standing water in the crack.
5. Allow Clemons **CRACK FILLER** to dry for 4 hours before sealing.
6. Seal with appropriate Clemons Sealer for your surface.

TECHNICAL DATA

VOC: 0g/L

Flash Point: N/A

HMIS

Health 0 Flammability 0

Reactivity 0 Protection 0

PRECAUTIONS

Protect from freezing. Apply when air and surface temperature is above 50F and below 90F. Do not apply when rain is expected within 4 hours. Discard after use. Opened bottle will not store well.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052