

A1 SOLVENT

DESCRIPTION

A1 SOLVENT can be applied to solvent-based concrete sealers to:

1. Release moisture from sealed concrete.
 - Roll, brush, or spray onto the surface of a solvent-based acrylic sealer.
2. Dissolve bubbles in the film by re-emulsifying the sealer.
 - Roll, brush, or spray onto the surface of a solvent-based acrylic sealer.
3. Clean up tools.
 - Soak metal tools briefly, wipe clean, and allow to dry.
4. Thin a sealer.
 - **A1 Solvent** will thin solvent-based acrylic sealers. Add sealer to the solvent at a 4:1 ratio and stir for a minute.
5. Use **A1 SOLVENT** between sealing years to rejuvenate a seal.

FEATURES

- ★Fast Acting
- ★Cuts through film build-up
- ★Clean tools

APPLICATION

Apply **A1 SOLVENT** with a roller, brush, or sprayer. Apply only when the surface, and air temperatures, are above 50° F and below 90° F. Clean all dirt, wax, grease, oil, and other contaminants from the surface. Pour the solvent into a metal, or solvent-resistant, paint tray. Use a short-nap, solvent-resistant, roller to apply **A1 SOLVENT** to the areas of sealer at a coverage rate of approximately 200 ft²/gallon. Apply steady, even, strokes to the solvent. Do not "over roll", back and forth aggressively, as this can cause bubbling. After a few minutes, the **A1 SOLVENT** will re-melt the sealer. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours.

HMIS

Health	2	Flammability	3
Reactivity	0	Protection	B

PRECAUTIONS

Flammable! Contains Petroleum distillates. Keep away from heat and flames. Use only with adequate ventilation. Avoid prolonged breathing of vapors and contact with skin. Keep out of eyes and mouth. **WEAR RUBBER GLOVES AND SAFETY GLASSES.** Keep the container closed when not in use. In case of a spill, absorb and dispose of the material in accordance with local applicable regulations. **KEEP AWAY FROM CHILDREN!**

DISCLAIMER: Since the manufacturer has no control over handling, use, or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. The manufacturer retains the right to venue.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052