

SUPER SEAL PAVER SEALER

DESCRIPTION

SUPER SEAL PAVER SEALER is a high solids (25%), styrene-acrylic copolymer solution formulated to achieve both a protective and decorative finish for concrete pavers. SUPER SEAL PAVER SEALER adds UV protection to prevent yellowing and sun fade. It acts as a joint sand stabilizer reducing erosion and preventing weeds.

FEATURES

★High Gloss

★Wet Look

★High Solids

★U.V. Resistant

PREPARATION

Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar solvent-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete pavers with CLEANER DEGREASER & NEUTRALIZER. Use a bristle brush for heavily oiled spots. Rinse well with a pressure washer. Sweep away any loose sand. Allow 24 hours to dry.

Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause bubbles or streaking to form.

Sand should be installed prior to sealing. Polymeric sand is recommended and should be properly cured before sealing. Regular sand should be plate compacted to reduce pickup on roller. Allow surface to fully dry after sand is installed.

APPLICATION

For best results apply with a solvent-resistant sprayer, roller or brush. Brush may be used where roller won't reach. Do not pour directly from can to pavers. Apply evenly from can or other metal container with appropriate roller. Use a medium nap roller. Keep roller soaked by dipping on every stroke. Every few feet turn perpendicular to the first coat, and cross roll without re-dipping. Wait until the surface is tack-free before applying a second coat. If the continual dipping with the first coat gives a heavy application, then cross-rolling allows for an even application. If spraying, use a solvent resistant sprayer and clean up immediately with aromatic solvent such as A1 SOLVENT or Xylene. Hold conical spray tip no more than 8" from surface. Do not thin product. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Do not apply if rain is imminent. Cooler temperatures or increased humidity will slow the drying time.

NET COVERAGE RATE

Two thin coats are recommended. Apply to pavers at a rate of 75-100 ft² per gallon including all coats.

TECHNICAL DATA

VOC: Standard <700 g/L
Low VOC <350g/L

Flash Point: Standard 105° F
Low VOC 40°F

HMIS

Health	2	Flammability	2 (Low VOC = 3)
Reactivity	0	Protection	B

CLEANUP

Clean tools with A1 Solvent or Xylene.

MAINTENANCE

Clean sealed surface with water only. Reseal surface as needed but no more than every two years to prevent buildup of sealer.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052