Tint Pack

Section 1	Product Description
Product Name:	Tint Pack
Recommended Use:	Additive for coloring sealer
Supplier:	Clemons Concrete Coatings, 505 Cave Road, Nashville, TN 37210, 615-872-9099
Emergency Phone:	INFOTRAC 1-800-535-5053

Section 2 Hazard identification

Category 3 Flammable Liquid Category 2 Skin Irritation Category 2A Eye Irritation Category 1B Carcinogenicity Category 1B Germ Cell Mutagenicity Category 3 Specific Target Organ Acute Toxicity (Central Nervous System) Category 2 Specific Target Organ Chronic Toxicity (Liver, Kidney, Central Nervous System) Category 1 Aspiration Hazard



Signal Word:

Danger

Hazard Statements:

H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways H315 Causes skin irritation H319 Causes serious eye irritation H331 Toxic if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H340 May cause genetic defects

H351 Suspected of causing cancer

H373 May cause damage to organs (liver, kidney, central nervous system) through prolonged exposure

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking

P233 Keep container tightly closed

P260 Do not breathe mist/vapors/spray

P264 Wash skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P281 Use personal protective equipment as required

Response:

P301+P310+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician

Safety Data Sheet

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340+P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician.

P305+p351+p338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash before reuse

P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction Storage:

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. Disposal:

P501 Dispose of contents/container in accordance with local/federal regulations.

Section 3	Composition/	on Ingredients	
	CAS #	OSHA PEL(TWA)	ACGIH(TLV

Light Solvent Naphtha

OSHA PEL(TWA) 64742-95-6 None Established

ACGIH(TLV-TWA) None Established

W<u>t.%</u> 0.0 - 80.0

Section 4

First Aid Measures

Emergency First Aid Procedures

Skin: Clean material from skin with acetone, then wash with soap and water followed by moisturizer.

Eyes: Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Call a physician if irritation persists.

Inhalation: Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention if irritation persists. Ingestion: DO NOT INDUCE VOMITING. Give large quantities of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

Section 5 **Firefighting Procedures**

Extinguishing Media: Dry chemical, CO2, foam, water fog.

Flash Point (TCC): 0° F

Flammable Limits (% volume in air for solvents): LEL=1.0 UEL=13.0

Special Fire Fighting Procedures: Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources.

Section 6 **Spill or Leak Procedures**

Steps to Take if Material is Released or Spilled: No health affects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Absorb spillage in suitable inert material. Sweep or scrape up and containerize.

Section 7 Handling and Storage

Normal Handling: Always use good industrial hygiene practices and safety guidelines.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.

Waste Disposal Method: Dispose of material in accordance with federal, state, and local guidelines.

Special Precautions: Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld near the containers.

Protection Information Section 8

Respiratory Protection: Use NIOSH-approved organic vapor respirator when exposure levels cannot be maintained below limits or the chance of mist inhalation is present.

Ventilation: Provide adequate mechanical ventilation to keep exposure levels below TLV's.

Protective Gloves: Wear impervious chemical gloves.

Eye Protection: Wear chemical safety glasses.

Other Protective Clothing or Equipment: As needed to prevent repeated/prolonged contact.

Work/Hygienic Practices: Use only in adequately-ventilated area unless recommended respiratory protection is

Safety Data Sheet

used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

Section 9 Physical Data

Appearance: Colored liquid Odor: Typical hydrocarbon or ketone Odor Threshold: No data available pH: None Freezing/Melting Point: <-70° C Boiling Point: >125° F Flash Point: 0° F Evaporation Rate: No data available Flammability (solid, gas): Flammable liquid Upper/lower Flammability: 1.0-13.0 (% vol. in air) Vapor Pressure: 185 mm Hg @ 20° C Vapor Density (Air=1): 2.0 Relative Density: 0.95 - 1.20 g/cc Solubility: Low solubility in water Partition Coefficient: Not determined Auto-ignition Temperature: 850° F Decomposition temperature: Not determined Viscosity: Not determined Specific Gravity (H20=1): 0.95 - 1.20

Section 10 Reactivity Data

Reactivity: Conditions to avoid: Hazardous decomposition products: Hazardous Polymerization: Incompatibility (Materials to Avoid):

Stable. Prevent vapor accumulation. Avoid heat, sparks, and flames. Carbon monoxide and carbon dioxide Should not occur. Strong acids and oxidizing materials.

Section 11 Toxicity Data

Routes of Exposure: Inhalation, ingestion, eyes, and skin. Acute Toxicity Lethal Doses (ATE):

LC50 (inhl) No data available

LD50 (oral) No data available

LD50 (skin) No data available

Health Hazards:

Acute: Minimally toxic. May cause eye, skin, gastrointestinal, and lung irritation. May cause central nervous system excitation followed by depression.

Chronic: Prolonged and repeated exposures to high concentrations may cause hearing loss. May cause liver and kidney damage.

Skin Contact: May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin, which may result in a burning sensation and a dried, cracked appearance.

Eye Contact: May cause redness, tearing, blurred vision, and irritation of the eyes.

Inhalation: Overexposure may cause headache, nausea, dizziness, and loss of coordination.

Ingestion: May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

Carcinogen: Contains trace amounts of Ethyl Benzene (<0.075% of total formulation by weight), which is considered a carcinogen by IARC. It has caused cancer in laboratory animals. The relevance of these findings to humans is uncertain.

Aggravation of Pre-existing Conditions: Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

Section 12 Ecological Data

Acute Toxicity to Fish: No data available Acute Toxicity to Aquatic Invertebrates: No data available Toxicity to Aquatic Plants: No data available Toxicity to Microorganisms: No data available

Safety Data Sheet

Chronic Toxicity to Fish: No data available Chronic Toxicity to Aquatic Invertebrates: No data available Persistence and Degradability: Expected to degrade readily and rapidly in the presence of oxygen Bioaccumulation Potential: This material is not expected to bioaccumulate Mobility in the Soil: Adsorbs in soil Other Adverse Effects: None established

Section 13 **Disposal Information**

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with all Federal, State, and Local regulations.

Section 14 **Transport Information**

All Modes: Proper Shipping Name: Paint Hazard Class: 3 **UN:** UN1263 Packing Group: PGII Marine Pollutant: No.

Section 15 **Regulatory Information**

SARA 311/312: Yes. (Fire, Acute, Chronic) OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200). TSCA: Components of this material are either listed or are exempt from the EPA TSCA Inventory of Chemical Substances

Substances.				
California Proposition 65:	WARNING! This product contains a chemical known to the State of California to cause cancer.			
		t contains a chemic	cal known to the State of California to	
	cause birth defects or other reproductive harm.			
Massachusetts Right To Know:	Petroleum distillates, Aliphatic	64742-47-8	0.0 - 80.0	
	VM & P Naphtha	8032-32-4	0.0 - 80.0	
	Stoddard Solvent	8052-41-3	0.0 - 80.0	
	Isobutyl Acetate	110-19-0	0.0 - 80.0	
	Dimethyl ketone	67-64-1	5.0 - 50.0	
Pennsylvania Right To Know:	Petroleum distillates, Aliphatic	64742-47-8	0.0 – 80.0	
	VM & P Naphtha	8032-32-4	0.0 - 80.0	
	Stoddard Solvent	8052-41-3	0.0 - 80.0	
	Isobutyl Acetate	110-19-0	0.0 - 80.0	
	Dimethyl ketone	67-64-1	5.0 - 50.0	
New Jersey Right To Know:	Petroleum distillates, Aliphatic	64742-47-8	0.0 – 80.0	
	VM & P Naphtha	8032-32-4	0.0 - 80.0	
	Stoddard Solvent	8052-41-3	0.0 - 80.0	
	Isobutyl Acetate	110-19-0	0.0 - 80.0	
	Dimethyl ketone	67-64-1	5.0 - 50.0	

Section 16 **Additional Information**

The regulatory information provided is not intended to be comprehensive. Other Federal, State and Local regulations may apply to this material.

DISCLAIMER: Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, manufacturer makes no representations as to the completeness or accuracy thereof.