

ACETONE

DESCRIPTION

ACETONE is standard in the industry for cleaning tools and surfaces when working with epoxy resins. ACETONE can be used in Low VOC sealers and is used to mix with SUPER COLOR and SUPER DYE. It is also the recommended solvent for removing greases and waxes from surfaces which are to be bonded, repaired, or primed.

LIMITATIONS

ACETONE will not remove 2-component resins from tools, brushes, etc., after the resin has set. It is not recommended for thinning 2-component systems or gel coats. Although ACETONE may be used as a thinner for solution acrylics, we do not recommend using this with Clemons' sealers. ACETONE is a highly flammable liquid and must be handled with the same care given to other flammable liquids.

TECHNICAL INFORMATION

Appearance - Clear water white liquid
Specific Gravity @ 25C- 0.7860-0.7890
Purity, Wt. % - 99.5 Min
Water, Wt. % - 0.5 Max
Non-volatile Matter, ppm - 10 Max
Water Solubility - Miscible

STORAGE

Keep out of Reach of Children. EXTREMELY FLAMMABLE! All containers should be properly labeled to prevent accidental ingestion or improper disposal. Individuals should re-seal any partly used material back in the original container. Store under cool, dry conditions away from open flames and high temperatures. Avoid storing in direct sunlight. For more detailed instructions on storage, please see the SDS Sheet.

SAFETY & HANDLING

Acetone contains ingredients that could be harmful if mishandled. Highly flammable vapors may travel along surfaces to distant ignition sources. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Individuals should wash with soap and water before eating, drinking, or using toilet facilities. Individuals should observe conditions of good industrial hygiene and safe working practices. For more detailed instructions on handling please refer to the SDS Sheet.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052