

Super Wax Polish

Water Based Acrylic and Wax Copolymer

DESCRIPTION

SUPER WAX POLISH is a water-based acrylic & wax co-polymer which forms a tough abrasion resistant clear non-yellowing top coat polish to protect existing sealers and finishes. This co-polymer offers excellent gloss and can be stripped with conventional wax polish removers. Its toughness protects the existing finish and acts as a sacrificial coating for the hard sealed substrate. SUPER WAX POLISH resists scuffs and marks while enhancing the gloss of the finish below. SUPER WAX POLISH also increases slip resistance. SUPER WAX POLISH is formulated as follows:

SUPER WAX POLISH GLOSS provides a high gloss showroom finish.

SUPER WAX POLISH MATTE provides a matte finish for a more natural look.

FEATURES

- ★ Reduces the need to reseal surfaces
- ★ Durable scuff resistant coating
- ★ Increased slip resistance
- ★ Non-yellowing

PREPARATION

Surface should be clean and sealed

APPLICATION

Apply with lamb's wool or microfiber applicator. Two or three initial coats may be preferred. Allow 30-60 minutes between coats to dry. Buffing with high speed buffing machine will maximize luster of SUPER WAX POLISH. Allow 4 hours to cure and dry before foot traffic resumes. Re-apply as needed.

NET COVERAGE RATE

1,000 ft² per gallon per coat. 2-3 coats may be preferred.

TECHNICAL DATA

VOC: standard 0g/L
Flash Point: N/A

HMIS

Health	0	Flammability	0
Reactivity	0	Protection	A

CLEANUP

Clean up tools with water

MAINTENANCE

Cleaning of the polished surface should be accomplished using ONLY water or Pledge Multi-surface cleaner and a soft mop. DO NOT USE aggressive cleaning agents, such as citrus-based, ammonia, or 409/Simple Green, bleach cleaners. Using an abrasive cleaning tool will scratch and dull the polished surface, requiring re-application of SUPER WAX POLISH to restore the shine.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Clemons Concrete Coatings warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052