

# Safety Data Sheet

## Top Coat

### Section 1

### Product Description

Product Name: Top Coat  
Recommended Use: Clear Topcoat for Solid Color Super Sealer Stain  
Supplier: Clemons Concrete Coatings, 505 Cave Road, Nashville, TN 37210, 615-872-9099  
Emergency Phone: INFOTRAC 1-800-535-5053

### Section 2

### Hazard identification

Category 3 Flammable Liquid

Category 5 Acute Inhalation Toxicity

Category 2 Skin Irritation

Category 2A Eye Irritation

Category 1B Carcinogenicity

Category 1B Germ Cell Mutagenicity

Category 2 Reproductive Toxicity

Category 3 Specific Target Organ Acute Toxicity (Central Nervous System)

Category 2 Specific Target Organ Chronic Toxicity (Liver, Kidney, Central Nervous System)

Category 1 Aspiration Hazard

Category 2 Acute Aquatic Toxicity



Signal Word:

Danger

Hazard Statements:

H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways  
H315 Causes skin irritation  
H319 Causes serious eye irritation  
H333 May be harmful if inhaled  
H335 May cause respiratory irritation  
H336 May cause drowsiness or dizziness  
H340 May cause genetic defects  
H351 Suspected of causing cancer  
H360 May damage fertility or the unborn child  
H373 May cause damage to organs (liver, kidney, central nervous system) through prolonged exposure  
H401 Toxic to aquatic life

Precautionary statements:

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking  
P233 Keep container tightly closed  
P260 Do not breathe mist/vapors/spray  
P264 Wash skin thoroughly after handling

## Safety Data Sheet

P271 Use only outdoors or in a well-ventilated area

P281 Use personal protective equipment as required

### Response:

P301+P310+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340+P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician.

P305+p351+p338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash before reuse

P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction

### Storage:

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### Disposal:

P501 Dispose of contents/container in accordance with local/federal regulations.

## Section 3

### Composition/ Information on Ingredients

	<u>CAS #</u>	<u>OSHA PEL(TWA)</u>	<u>ACGIH(TLV-TWA)</u>	<u>Wt. %</u>
Acrylic polymers	Proprietary	Not established	Not established	20.0 – 30.0
Petroleum Naphtha, Hydrodesulfurized heavy	64742-82-1	500 ppm	100 ppm	1.0 – 80.0
Naphtha, medium aliphatic	64742-88-7	500 ppm	200ppm	1.0 – 80.0
Stoddard Solvent	8052-41-3	500 ppm	100 ppm	1.0 – 80.0
Naphtha, hydrotreated heavy	64742-48-9	500 ppm	Not available	1.0 – 80.0
Naphtha, light aromatic	64742-95-6	500 ppm	200 ppm	7.5 – 22.6
1,2,4-Trimethylbenzene	95-63-6	25 ppm	25 ppm	0.7 – 7.5
Benzene, -trimethyl	25551-13-7	25 ppm	25 ppm	0.7 – 3.8
Nonane	111-84-2	200 ppm	200 ppm	0.7 – 3.8
1,3,5-Trimethylbenzene	108-67-8	25 ppm	25 ppm	0.7 – 3.8
1,2,3-Trimethylbenzene	526-73-8	25 ppm	25 ppm	0.7 – 3.8
Propylbenzene	103-65-1	Not established	Not established	0.7 – 3.8
Mixed Xylenes	1330-20-7	100 ppm	100 ppm	0.0 – 0.7
Cumene	98-82-8	50 ppm	50 ppm	0.0 – 0.7
Ethylbenzene	100-41-4	100 ppm	20 ppm	0.0 – 0.4
Naphthalene	91-20-3	10 ppm	10 ppm	0.0 – 0.4
Diocetyl Phthalate	117-81-7	5 ppm	5 ppm	0.1 – 0.2

## Section 4

### First Aid Measures

#### Emergency First Aid Procedures

**Skin:** Clean material from skin with acetone, then wash with soap and water followed by moisturizer.

**Eyes:** Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Call a physician if irritation persists.

**Inhalation:** Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention if irritation persists.

**Ingestion:** DO NOT INDUCE VOMITING. Give large quantities of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

## Section 5

### Firefighting Procedures

**Extinguishing Media:** Dry chemical, CO<sub>2</sub>, foam, water fog.

**Flash Point (TCC):** 105° F

**Flammable Limits (% volume in air for solvents):** LEL=1.1 UEL=7.0

**Special Fire Fighting Procedures:** Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources.

# Safety Data Sheet

## Section 6 Spill or Leak Procedures

**Steps to Take if Material is Released or Spilled:** No health effects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Absorb spillage in suitable inert material. Sweep or scrape up and containerize.

## Section 7 Handling and Storage

**Normal Handling:** Always use good industrial hygiene practices and safety guidelines.

**Storage:** Store material in its original container. Keep containers tightly closed when not in use. Keep material away from open flame, sparks, or other sources of heat and ignition.

**Waste Disposal Method:** Dispose of material in accordance with federal, state, and local guidelines.

**Special Precautions:** Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld near the containers.

## Section 8 Protection Information

**Respiratory Protection:** Use NIOSH-approved organic vapor respirator when exposure levels cannot be maintained below limits or the chance of mist inhalation is present.

**Ventilation:** Provide adequate mechanical ventilation to keep exposure levels below TLV's.

**Protective Gloves:** Wear impervious chemical gloves.

**Eye Protection:** Wear chemical safety glasses.

**Other Protective Clothing or Equipment:** As needed to prevent repeated/prolonged contact.

**Work/Hygienic Practices:** Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

## Section 9 Physical Data

**Appearance:** Clear liquid

**Odor:** Typical hydrocarbon

**Odor Threshold:** No data available

**pH:** None

**Freezing/Melting Point:** -76° C

**Boiling Point:** >310° F

**Flash Point:** 105° F

**Evaporation Rate:** 0.14 (butyl acetate=1)

**Flammability (solid, gas):** Flammable liquid

**Upper/lower Flammability:** 1.1-7.0 (% vol. in air)

**Vapor Pressure:** 0.62 mm Hg @ 20° C

**Vapor Density (Air=1):** 4.9

**Relative Density:** 0.85 g/cc

**Solubility:** Negligible solubility in water

**Partition Coefficient:** Not determined

**Auto-ignition Temperature:** 444°F- 539° F

**Decomposition temperature:** Not determined

**Viscosity:** Not determined

**Specific Gravity (H2O=1):** 0.85

## Section 10 Reactivity Data

**Reactivity:** Stable.

**Conditions to avoid:** Prevent vapor accumulation. Avoid heat, sparks, and flames.

**Hazardous decomposition products:** Carbon monoxide and carbon dioxide

**Hazardous Polymerization:** Should not occur.

**Incompatibility (Materials to Avoid):** Strong acids and oxidizing materials.

## Section 11 Toxicity Data

**Routes of Exposure:** Inhalation, ingestion, eyes, and skin.

**Acute Toxicity Lethal Doses (ATE):**

LC50 (inhl) 24.1 mg/l

LD50 (oral) 6579 mg/kg

LD50 (skin) 6579 mg/kg

# Safety Data Sheet

## Health Hazards:

**Acute:** Minimally toxic. May cause eye, skin, gastrointestinal, and lung irritation. May cause central nervous system excitation followed by depression.

**Chronic:** Prolonged and repeated exposures to high concentrations may cause hearing loss. May cause liver and kidney damage.

**Skin Contact:** May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin, which may result in a burning sensation and a dried, cracked appearance.

**Eye Contact:** May cause redness, tearing, blurred vision, and irritation of the eyes.

**Inhalation:** Overexposure may cause headache, nausea, dizziness, and loss of coordination.

**Ingestion:** May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

**Carcinogen:** Contains trace amounts of Ethyl Benzene (<0.075% of total formulation by weight), which is considered a carcinogen by IARC. It has caused cancer in laboratory animals. The relevance of these findings to humans is uncertain.

**Aggravation of Pre-existing Conditions:** Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

## Section 12 Ecological Data

**Acute Toxicity to Fish:** LC50 10.1 mg/L (calculated)

**Acute Toxicity to Aquatic Invertebrates:** LC50 4.4 mg/L (calculated)

**Toxicity to Aquatic Plants:** EC50 3.20 mg/L (calculated)

**Toxicity to Microorganisms:** No data available

**Chronic Toxicity to Fish:** No data available

**Chronic Toxicity to Aquatic Invertebrates:** No data available

**Persistence and Degradability:** Expected to degrade readily and rapidly in the presence of oxygen

**Bioaccumulation Potential:** This material is not expected to bioaccumulate

**Mobility in the Soil:** Adsorbs in soil

**Other Adverse Effects:** None established

## Section 13 Disposal Information

**Waste Disposal Method:** Liquid material is an ignitable waste (D001). Dispose of material in accordance with all Federal, State, and Local regulations.

## Section 14 Transport Information

**For Domestic (US) Ground Transport:** Non-Regulated Material in <119-gallon containers

**Proper Shipping Name:** Paint

**Hazard Class:** 3

**UN:** UN1263

**Packing Group:** PGIII

**Marine Pollutant:** No

## Section 15 Regulatory Information

**SARA 311/312:** Yes. (Fire, Acute, Chronic)

**OSHA:** This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200).

**TSCA:** Components of this material are either listed or are exempt from the EPA TSCA Inventory of Chemical Substances.

**California Proposition 65:** WARNING! This product contains a chemical known to the State of California to cause cancer.

98-82-8	Cumene
100-41-4	Ethylbenzene
91-20-3	Naphthalene
71-43-2	Benzene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

71-43-2	Benzene
117-81-7	bis(2-Ethylhexyl) phthalate

## Safety Data Sheet

<b>Massachusetts Right To Know:</b>	Stoddard Solvent	8052-41-3	1.0 – 80.0
	1,2,4-Trimethylbenzene	95-63-6	0.7 – 7.5
	Benzene, -trimethyl	25551-13-7	0.7 – 3.8
	Nonane	111-84-2	0.7 – 3.8
	1,3,5-Trimethylbenzene	108-67-8	0.7 – 3.8
	Mixed Xylenes	1330-20-7	0.0 – 0.7
<b>Pennsylvania Right To Know:</b>	Petroleum Naphtha, Hydrodesulfurized heavy	64742-82-1	1.0 – 80.0
	Naphtha, medium aliphatic	64742-88-7	1.0 – 80.0
	Stoddard Solvent	8052-41-3	1.0 – 80.0
	Naphtha, hydrotreated heavy	64742-48-9	1.0 – 80.0
	Naphtha, light aromatic	64742-95-6	7.5 – 22.6
	1,2,4-Trimethylbenzene	95-63-6	0.7 – 7.5
	Benzene, -trimethyl	25551-13-7	0.7 – 3.8
	Nonane	111-84-2	0.7 – 3.8
	1,3,5-Trimethylbenzene	108-67-8	0.7 – 3.8
	Propylbenzene	103-65-1	0.7 – 3.8
	Mixed Xylenes	1330-20-7	0.0 – 0.7
	Cumene	98-82-8	0.0 – 0.7
	Ethylbenzene	100-41-4	0.0 – 0.4
	Naphthalene	91-20-3	0.0 – 0.4
	Diethyl Phthalate	117-81-7	0.1 – 0.2
<b>New Jersey Right To Know:</b>	Petroleum Naphtha, Hydrodesulfurized heavy	64742-82-1	1.0 – 80.0
	Naphtha, medium aliphatic	64742-88-7	1.0 – 80.0
	Stoddard Solvent	8052-41-3	1.0 – 80.0
	Naphtha, hydrotreated heavy	64742-48-9	1.0 – 80.0
	Naphtha, light aromatic	64742-95-6	7.5 – 22.6
	1,2,4-Trimethylbenzene	95-63-6	0.7 – 7.5
	Nonane	111-84-2	0.7 – 3.8
	Propylbenzene	103-65-1	0.7 – 3.8
	Mixed Xylenes	1330-20-7	0.0 – 0.7
	Cumene	98-82-8	0.0 – 0.7
	Ethylbenzene	100-41-4	0.0 – 0.4
	Naphthalene	91-20-3	0.0 – 0.4
	Diethyl Phthalate	117-81-7	0.1 – 0.2

### Section 16 Additional Information

The regulatory information provided is not intended to be comprehensive. Other Federal, State and Local regulations may apply to this material.

**DISCLAIMER:** Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, manufacturer makes no representations as to the completeness or accuracy thereof.