

SUPER GUARD

Water-Based Urethane-Acrylic Sealer for Polished Concrete

DESCRIPTION

SUPER GUARD is a water-based urethane-acrylic co-polymer which forms a tough abrasion resistant clear non-yellowing top coat to protect polished concrete finishes. This co-polymer offers excellent gloss and chemical resistance. Its toughness provides a barrier between colored polished concrete and subsequent easily-strippable floor polishes. SUPER GUARD resists scuffs and marks while allowing for periodic buffing and scrub/recoat maintenance.

FEATURES

- ★ Protects polished floors from staining
- ★ Non-yellowing
- ★ Provides temporary protection from water and spills
- ★ Durable scuff resistant coating
- ★ Increased slip resistance

PREPARATION

Surface should be clean and dry.

APPLICATION

Apply with a pump sprayer and lamb's wool or microfiber applicator. Two or three initial coats may be preferred. Allow 45 -60 minutes between coats to dry. Buffing with high speed buffing machine will maximize luster of SUPER GUARD. Allow 4 hours to cure and dry before foot traffic resumes. Re-apply as needed.

NET COVERAGE RATE

1,000 ft² per gallon per coat. Two or three coats may be preferred

TECHNICAL DATA

VOC: standard <100g/L
Flash Point: N/A
Solids: 19% +/- 0.5%

HMIS

Health	0	Flammability	0
Reactivity	0	Protection	A

CLEANUP

Clean tools with water.

MAINTENANCE

Cleaning of the polished surface should be accomplished using ONLY water or Pledge Multi-surface cleaner and a soft mop. DO NOT USE aggressive cleaning agents, such as citrus-based, ammonia, or 409/Simple Green, bleach cleaners. Using an abrasive cleaning tool will scratch and dull the polished surface, requiring re-application of Super Guard to restore the shine.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Clemons Concrete Coatings warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052